





### Features

- Epitaxial planar die construction
- Complimentary to MMBT3906
- Ultra-small surface mount package

### Mechanical Data

- Case: SOT-23
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208



SOT-23

### Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
MMBT3904	SOT-23	3000 pcs / Tape & Reel	1AM

### Maximum Ratings (@ T<sub>A</sub> = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Breakdown Voltage	V <sub>CBO</sub>	60	V
Collector-Emitter Breakdown Voltage	V <sub>CEO</sub>	40	V
Emitter-Base Breakdown Voltage	V <sub>EBO</sub>	6	V
Continuous Collector Current	I <sub>C</sub>	0.2	A
Peak Collector Current	I <sub>CM</sub>	0.2	A
Peak Base Current	I <sub>BM</sub>	0.1	A

### Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P <sub>D</sub>	250	mW
Thermal Resistance Junction-to-Air <sup>*1</sup>	R <sub>θJA</sub>	386	°C/W
Thermal Resistance Junction-to-Case <sup>*1</sup>	R <sub>θJC</sub>	221	°C/W
Thermal Resistance Junction-to-Lead <sup>*1</sup>	R <sub>θJL</sub>	168	°C/W
Ambient Temperature	T <sub>A</sub>	-55 ~ +150	°C
Operating junction Temperature	T <sub>J</sub>	-65 ~ +150	°C
Storage Temperature Range	T <sub>STG</sub>	-65 ~ +150	°C

Note 1: The data tested by surface mounted on a 15mm \* 15mm \* 1mm FR4-epoxy P.C.B



**Electrical Characteristics** (@ T<sub>A</sub> = 25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	V <sub>(BR)CBO</sub>	I <sub>C</sub> = 10μA, I <sub>E</sub> = 0	60	-	-	V
Collector-Emitter Breakdown Voltage	V <sub>(BR)CEO</sub>	I <sub>C</sub> = 100μA, I <sub>B</sub> = 0	40	-	-	V
Emitter-Base Breakdown Voltage	V <sub>(BR)EBO</sub>	I <sub>E</sub> = 10μA, I <sub>C</sub> = 0	6	-	-	V
Collector Cut-off Current	I <sub>CBO</sub>	V <sub>CB</sub> = 30V, I <sub>E</sub> = 0	-	-	50	nA
Emitter Cut-off Current	I <sub>EBO</sub>	V <sub>EB</sub> = 6V, I <sub>C</sub> = 0	-	-	50	nA
DC Current Gain	h <sub>FE</sub>	V <sub>CE</sub> = 1V, I <sub>C</sub> = 0.1mA	60	-	-	-
		V <sub>CE</sub> = 1V, I <sub>C</sub> = 1mA	80	-	-	-
		V <sub>CE</sub> = 1V, I <sub>C</sub> = 10mA	100	-	300	-
		V <sub>CE</sub> = 1V, I <sub>C</sub> = 50mA	60	-	-	-
		V <sub>CE</sub> = 1V, I <sub>C</sub> = 100mA	30	-	-	-
Collector-emitter Saturation Voltage	V <sub>CE(sat)</sub>	I <sub>C</sub> = 10mA, I <sub>B</sub> = 1mA	-	-	0.2	V
		I <sub>C</sub> = 50mA, I <sub>B</sub> = 5mA	-	-	0.3	V
Base-emitter Saturation Voltage	V <sub>BE(sat)</sub>	I <sub>C</sub> = 10mA, I <sub>B</sub> = 1mA	-	-	0.85	V
		I <sub>C</sub> = 50mA, I <sub>B</sub> = 5mA	-	-	0.95	V
Transition Frequency	f <sub>T</sub>	I <sub>C</sub> = 10mA, V <sub>CE</sub> = 20V	300	-	-	MHz
Collector Output Capacitance	C <sub>OBO</sub>	V <sub>CB</sub> = 5V, I <sub>E</sub> = 0, f = 1MHz	-	-	4	pF
Input Capacitance	C <sub>IBO</sub>	V <sub>EB</sub> = 0.5V, I <sub>C</sub> = 0, f = 1MHz	-	-	8	pF
Noise Figure	N <sub>F</sub>	V <sub>CE</sub> = 5V, I <sub>C</sub> = 100μA, R <sub>S</sub> = 1kΩ f = 10Hz to 15.7kHz	-	-	5	dB
Delay Time	t <sub>d</sub>	V <sub>CC</sub> = 3V, I <sub>C</sub> = 10mA	-	-	35	ns
Rise Time	t <sub>r</sub>	V <sub>BE(OFF)</sub> = -0.5V, I <sub>B1</sub> = 1mA	-	-	35	ns
Storage Time	t <sub>s</sub>	V <sub>CC</sub> = 3V, I <sub>C</sub> = 10mA	-	-	200	ns
Fall Time	t <sub>f</sub>	I <sub>B1</sub> = I <sub>B2</sub> = 1mA	-	-	50	ns



### Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1  $h_{FE}$  vs.  $I_C$




Fig 2  $V_{CE(sat)}$  vs.  $I_C$




Fig 3  $V_{BE(sat)}$  vs.  $I_C$




Fig 4  $V_{BE(ON)}$  vs.  $I_C$




Fig 5  $I_C$  vs.  $V_{CE}$






Fig 6  $P_D$  vs.  $T_A$




**Fig 7 C<sub>J</sub> vs. V<sub>R</sub>**

**Package Outline Dimensions** (Unit: mm)



SOT-23		
Dimension	Min.	Max.
A	2.70	3.10
B	1.10	1.50
C	0.9	1.1
D	0.3	0.5
E	0.35	0.48
G	1.80	2.00
H	0.02	0.1
J	0.05	0.15
K	2.20	2.60

**Package Outline Dimensions(SOT-23)** (Unit: mm)



Package	Reel	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)
SOT-23	3000pcs	7inch	45,000pcs	203×203×195	180,000pcs	438×438×220